NANA ENGINEERING

High Quality CY3 Type Current Sensor

Bipolar power supply PCB mounting

Features

Compact and lightweight

Low power consumption

Extended measuring range

Low cost

Measurable with DC and AC

Open Loop Type

RoHS Compliant

Specifications

Ta=25℃

Product name	Code:1174		CY3-20
	Symbol	Unit	
Nominal input current	If(n)	A	±20
Saturation current	If(s)	A	±30
Nominal Output Voltage	Vh	V	±2±0.020 [at If(n)]
Load resistance	RL	Ω	10k
Offset Voltage	Vo	V	0±0.040 [at 0A]
Supply Voltage	Vcc	V DC	±5±5%
Consumption Current	Icc	mA	±25 Max.
Response Speed	Trr	μsec	5 Max. [at di/dt=If(n)/μsec]
Thermal Drift of Vh		%/℃	±0.08 Max. [at If(n)]
Thermal Drift of Vo		mV/℃	±1 Max. [at 0A]
Dielectric Strength		kV	AC 2.5 [with 50 or 60 Hz 1min.]
Insulation Resistance		Ω	500M Min. [at 500V DC]
Operating Temperature	Ta	℃	-20 to +80
Storage Temperature	Ts	℃	-25 to +85
Hysteresis Error		mV	±20 Max. [at If --> 0]

Dimensions

Unit : mm



CY-21013

Product Name	Mass	Dφ
CY3-20	11g	1.4

Connection



NANA ENGINEERING CO.,LTD.
Machida 310 Irago building 4F
1-22-5 Morino, Machida-shi, Tokyo 194-0022
E-Mail : nanaeng_sales@nana-e.com
URL : http://www.nana-e.com

*The specification (in this catalogue) are subject to minor changes without prior notice.
The edition of March 2023