

## Features

Low thermal drift

Extended measuring range

Voltage detector for AC and DC

Excellent linearity

Completely insulated from the primary side

Closed Loop Type






## Specifications

Ta=25°C

Product name	Code:2255		HVT-C400
	Symbol	Unit	
Nominal input Voltage	Vin	V	±400
Saturation Voltage	Vin(s)	V	±560
Nominal Output current	Iout	mA	±25 [at Vin]
Offset current	I0	mA	0±0.15 [at 0V]
Supply Voltage	Vcc	V DC	±15±5%
Consumption Current	Icc	mA	18 + Iout
Response Speed	Trr	μ sec	50 Max.
Thermal Drift of Iout		mA	Within±0.35 [at between Ta=0 to 70°C]
Thermal Drift of I0		mA	Within±0.5 [at between Ta=0 to 70°C]
Dielectric Strength		kV	AC 2.5 [with 50 or 60 Hz 1min.]
Insulation Resistance		Ω	500M Min. [at 500V DC]
Operating Temperature	Ta	°C	0 to +70
Storage Temperature	Ts	°C	-25 to +85
Measuring resistance	Rm	Ω	30~100

## Dimensions

Unit : mm




Terminal Block Type[F2060AX-4P(M3)] Maker[FUJICON]

HVT-21035

Product Name  
HVT-C400

## Connection



NANA ENGINEERING CO.,LTD.

Machida 310 Irago building 4F  
1-22-5 Morino, Machida-shi, Tokyo 194-0022  
E-Mail : nanaeng\_sales@nana-e.com  
URL : <http://www.nana-e.com>